

THE **32AMP** RANGE

MAC ELEKTRA S.S.

The Revolutionary New Electrically Heated Mobile Pressure Wash

The MAC 32 Amp range is manufactured specifically for 32amp 400v power supplies, providing the ultimate best-in-class performance with a wide range of options



KEY SPECIFICATION

80°C Maximum Heat

10lt or 15lt/min Water Flow

16kW-24kW Heating Power

150bar or 200bar Pressure

400v, 32amp Power Supply



THE **32AMP** RANGE

MAC ELEKTRA S.S.



MAC 21TECH

USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC

SIEMENS

STANDARD FEATURES

- High quality heavy-duty stainless steel chassis
- High quality stainless steel hinged cover
- Featuring the MAC On Demand Heating System
- 120lt stainless steel insulated water tank
- Timed total stop shutdown system
- High temperature pump
- Low rewing 1450rpm motor
- Easy access for servicing
- Unrivalled heat performance
- Maximum temperature output of 80°C
- Highly accurate digital thermostat display
- Available from 16kW to 24kW

GO GREEN
CO₂ EMISSION FREE

MAC
ELECTRIC

THE
32AMP
RANGE

**THE MAC ELEKTRA
SSE1 & SSE4.1 ARE DESIGNED
TO RUN ON A STANDARD
32AMP POWER SUPPLY**

	ELEKTRA SSEM1	ELEKTRA SSEM4.1
Water Flow	10lt per minute	15lt per minute
Pressure	150bar, 2175psi	200bar, 3000psi
Motor Specification	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	16-24kW
Heating Elements	2 x 12kW	2 x 12kW
Volts Amps Watts	400v/32A/24kW	400v/32A/24kW
Shutdown System	Timed	Timed
Max. Temperature	80°C Maximum	80°C Maximum
Water Tank Size	120lt	120lt
Weight	200kg	215kg
Dimensions (h x w x d)	130 x 90 x 70cm	130 x 90 x 70cm