

MAC REVOLUTION ELECTRIC S.S.

Compact Electrically Heated Static Pressure Washer

- 80°C with market leading heat retention
- 170lt stainless steel insulated water tank
- Designed to run on a standard 32amp, 400v power supply
- Super-fast water reheating
- Premium quality 316L stainless steel cabinet



KEY SPECIFICATION

80°C Maximum Heat

10lt-15lt/min Water Flow

16kW-24kW Heating Power

150bar-200bar Pressure

Power Supply starting from
400v, 32amp



MAC REVOLUTION ELECTRIC S.S.



Image shows optional internal hose reel upgrade

MAC 21TECH

USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC



STANDARD FEATURES

- Low rewinding 1450rpm motor
- High temperature pump
- Easy access for servicing
- Double insulated stainless steel hot water tank
- Unrivalled heat performance
- Maximum temperature output 80°C
- Simple 24v controls
- Lockable stainless steel front door
- Hinged and removable cabinet front door and lid
- Available with MAC 18/24 Technology for 32amp, 400v power supplies

CABINET FINISH

- Full 316L stainless steel cabinet with lockable controls



THE MAC REVOLUTION SSE1, SSE3.1 & SSE4.1 ARE DESIGNED TO RUN ON A STANDARD 32AMP POWER SUPPLY

	REVOLUTION SSE1	REVOLUTION SSE2	REVOLUTION SSE3	REVOLUTION SSE3.1	REVOLUTION SSE4	REVOLUTION SSE4.1
Water Flow	10lt per minute	10lt per minute	13lt per minute	13lt per minute	15lt per minute	15lt per minute
Pressure	150bar, 2175psi	150bar, 2175psi	150bar, 2175psi	150bar, 2175psi	200bar, 3000psi	200bar, 3000psi
Motor Specification	3kW, 4hp, 1450rpm	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	24kW	24kW	16-24kW	24kW	16-24kW
Heating Elements	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW
Volts Amps Watts	400v/32A/24kW	400v/45A/27kW	400v/45A/30kW	400v/32A/24kW	400v/45A/30kW	400v/32A/24kW
Shutdown System	Timed	Timed	Timed	Timed total stop	Timed Total Stop	Timed
Max. Temperature	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum
Water Tank Size	170lt	170lt	170lt	170lt	170lt	170lt
Weight	200kg	200kg	210kg	215kg	215kg	215kg
Dimensions (h x w x d)	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm