

MAC PLANTMASTER ELECTRIC TWIN HOT

Twin User All Electric Static Pressure Washer

- Designed for dual-user operation
- 80°C with market leading heat retention
- 42kW Max. Heating Power in standby
- Perfect for large facilities such as factories that require multiple operators



KEY SPECIFICATION

80°C Maximum Heat

2 x 15lt/min water flow

42 / 36 / 30kW Heating Power

200bar Pressure

Power Supply 400v, 63amp



MAC PLANTMASTER ELECTRIC TWIN HOT

MAC21TECH

USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC

SIEMENS

STANDARD FEATURES

- Low revving 1450rpm motors
- High temperature pumps
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Unrivalled heat performance
- Maximum temperature output 80°C
- Highly accurate digital thermostat display
- Simple 24v controls
- Lockable powder coated steel front doors
- Hinged and removable cabinet front doors and lids

OPTIONAL ACCESSORIES AVAILABLE

- Full stainless steel cabinets
- Cold water rinse system



GO GREEN
CO₂ EMISSION FREE

MAC
ELECTRIC

	PLANTMASTER/TE2-SS	PLANTMASTER/TE2-PC
Water Flow	2 x 15lt per minute	2 x 15lt per minute
Pressure	200bar, 3000psi	200bar, 3000psi
Motor Specification	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	42 / 36 / 30kW	42 / 36 / 30kW
Heating Elements	3 x 12 kW, 1 x 6kW	3 x 12 kW, 1 x 6kW
Volts Amps Watts	400v, 63A, 24kW	400v, 63A, 24kW
Shutdown System	Automatic	Automatic
Max. Temperature	80°C Maximum	80°C Maximum
Chemical	High Pressure	High Pressure
Water Tank Size	375lt	375lt
Weight		

Dimensions (h x w x d)