

# MAC ELEKTRA S.S.

## The Revolutionary New Electrically Heated Mobile Pressure Washer

- Unbeatable all electric performance
- Up to 80°C with market leading heat retention
- High quality stainless steel chassis and cover
- 120lt stainless steel insulated water tank
- Super-fast water reheating



### KEY SPECIFICATION

- Electrically Heated Mobile
- 10, 13 & 15tr/min Water Flow
- 16kW-24kW Heating Power
- 80°C Maximum Temperature
- 400v, 32amp Power Supply



# MAC ELEKTRA S.S.



Image shows full stainless steel option

## MAC 21TECH

USER FRIENDLY CONTROL SYSTEM

### FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC



### STANDARD FEATURES

- High quality heavy-duty stainless steel chassis
- High quality stainless steel hinged cover
- Featuring the MAC On Demand Heating System
- 120lt stainless steel insulated water tank
- Timed total stop shutdown system
- High temperature pump
- Low rewing 1450rpm motor
- Easy access for servicing
- Unrivalled heat performance
- Maximum temperature output of 80°C
- Highly accurate digital thermostat display
- Available with MAC 18/24 Technology for 32amp



THE MAC ELEKTRA SSEM1 & SSEM4.1 ARE DESIGNED TO RUN ON A STANDARD 32AMP POWER SUPPLY

	ELEKTRA SSEM1	ELEKTRA SSEM2	ELEKTRA SSEM3	ELEKTRA SSEM4	ELEKTRA SSEM4.1
Water Flow	10lt per minute	10lt per minute	13lt per minute	15lt per minute	15lt per minute
Pressure	150bar, 2175psi	150bar, 2175psi	150bar, 2175psi	200bar, 3000psi	200bar, 3000psi
Motor Specification	3kW, 4hp, 1450rpm	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	24kW	24kW	24kW	16-24kW
Heating Elements	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW
Volts, Amps, Watts	400v/32A/24kW	400v/45A/24kW	400v/45A/30kW	400v/63A/42kW	400v/32A/24kW
Shutdown System	Timed Total Stop	Timed Total Stop	Timed Total Stop	Timed Total Stop	Timed Total Stop
Temperature	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum
Chemical	Low Pressure	Low Pressure	Low Pressure	Low Pressure	Low Pressure
Water Tank Size	120lt	120lt	120lt	120lt	120lt
Weight	140kg	140kg	140kg	140kg	140kg
Dimensions (l x w x h)	130cm x 60cm x 90cm	130cm x 60cm x 90cm	130cm x 60cm x 90cm	130cm x 60cm x 90cm	130cm x 60cm x 90cm