


MAC PLANTMASTER TWIN COLD S.S.

The Complete Twin Static Pressure Washer

- Large water tank as standard
- Full frost protection and cabinet lagging
- Automatic stop/start and leak detection
- Full stainless steel cabinet



KEY SPECIFICATION

Cold Water Twin Static

12ltr, 15ltr or 21ltr/min Water Flow

100bar or 200bar Pressure

230v or 400v Power Supply

Full Frost Protection

Auto Stop/Start



MAC PLANTMASTER TWIN COLD S.S.



Powder coated version shown above

THE
PlantMaster
RANGE



30 SECOND
AUTO STOP/START

MAC21TECH USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC

STANDARD FEATURES

- Full frost protection and cabinet lagging
- Leak detection
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motors
- Automatic stop/start system
- High pressure chemical system
- Large 18lt water tank
- Bypass and safety valve
- 24v low tension safety controls
- Mains power on lamp

CABINET FINISH

- Full stainless steel cabinet with lockable controls
- Lockable full stainless steel front door

ACCESSORIES

- Internal and external hose reels
- Upgraded water tanks
- Key fob and remote control systems
- Timed and non-timed chemical systems

	PLANTMASTER/SSTC1	PLANTMASTER/SSTC2	PLANTMASTER/SSTC3
Water Flow	2 x 12lt per minute	2 x 15lt per minute	2 x 21lt per minute
Pressure	2 x 100bar, 1500psi	2 x 200bar, 3000psi	2 x 200bar, 3000psi
Motor Specification	2 x 3hp, 1450rpm	2 x 7.5hp, 1450rpm	2 x 10hp, 1450rpm
Chemical	High Pressure	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Power	230v	400v	400v
Weight	160kg	180kg	200kg
Dimensions (h x w x d)	167 x 93 x 56cm	167 x 93 x 56cm	167 x 93 x 56cm