

THE **32AMP** RANGE

MAC PLANTMASTER ELECTRIC S.S.

Electrically Heated Static Pressure Washer

The MAC 32 Amp range is manufactured specifically for 32amp 400v power supplies, providing the ultimate best-in-class performance with a wide range of options



KEY SPECIFICATION

80°C Maximum Heat

10lt or 15lt/min Water Flow

16kW-24kW Heating Power

150bar or 200bar Pressure

400v, 32amp Power Supply



THE **32AMP** RANGE

MAC PLANTMASTER ELECTRIC S.S.



MAC21TECH

USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC

SIEMENS

STANDARD FEATURES

- Low revving 1450rpm motor
- High temperature pump
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Unrivalled heat performance
- Maximum temperature output 80°C
- Highly accurate digital thermostat display
- Simple 24v controls
- Available from 16kW to 24kW
- Lockable stainless steel front door
- Hinged and removable cabinet front door and lid

CABINET FINISH

- Full 316L stainless steel cabinet with lockable controls

OPTIONAL ACCESSORIES AVAILABLE

GO GREEN
CO₂ EMISSION FREE

MAC
ELECTRIC

THE
32AMP
RANGE

**THE MAC
PLANTMASTER
SSE1, SSE2.1
& SSE4.1 ARE
DESIGNED
TO RUN ON A
STANDARD
32AMP POWER
SUPPLY**

	PLANTMASTER SSE1	PLANTMASTER SSE2.1	PLANTMASTER SSE4.1
Water Flow	10lt per minute	13lt per minute	15lt per minute
Pressure	150bar, 2175psi	150bar, 2175psi	200bar, 3000psi
Motor Specification	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	16-24kW	16-24kW
Heating Elements	2 x 12kW	2 x 12kW	2 x 12kW
Volts Amps Watts	400v/32A/24kW	400v/32A/24kW	400v/32A/24kW
Shutdown System	Timed total stop	Timed total stop	Timed total stop
Max. Temperature	80 °C	80 °C	80 °C
Water Tank Size	375lt	375lt	375lt
Weight	250kg	260kg	260kg
Dimensions (h x w x d)	130 x 112 x 80cm	130 x 112 x 80cm	130 x 112 x 80cm