

THE **32AMP** RANGE

MAC REVOLUTION ELECTRIC

Compact Electrically Heated Static Pressure Washer

The MAC 32 Amp range is manufactured specifically for 32amp 400v power supplies, providing the ultimate best-in-class performance with a wide range of options



KEY SPECIFICATION

80°C Maximum Heat

10lt or 15lt/min Water Flow

16kW-24kW Heating Power

150bar or 200bar Pressure

400v, 32amp Power Supply



THE **32AMP** RANGE

MAC REVOLUTION ELECTRIC



Image shows optional internal hose reel upgrade

MAC 21TECH

USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC

SIEMENS

STANDARD FEATURES

- Low rewinding 1450rpm motor
- High temperature pump
- Easy access for servicing
- Double insulated stainless steel hot water tank
- Unrivalled heat performance
- Maximum temperature output 80°C
- Simple 24v controls
- Lockable powder coated steel front door
- Hinged and removable cabinet front door and lid
- Available from 16kW to 24kW

CABINET FINISH

- Powder coated steel cabinet with lockable controls
- High quality matte paint finish
- Zinc phosphate steel pre-treatment for weather proofing

GO GREEN
CO₂ EMISSION FREE

MAC
ELECTRIC

THE
32AMP
RANGE

**THE MAC
REVOLUTION
E1, E3.1 & E4.1
ARE DESIGNED
TO RUN ON A
STANDARD
32AMP POWER
SUPPLY**

	REVOLUTION E1	REVOLUTION E3.1	REVOLUTION E4.1
Water Flow	10lt per minute	13lt per minute	15lt per minute
Pressure	150bar, 2175psi	150bar, 2175psi	200bar, 3000psi
Motor Specification	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	16-24kW	16-24kW
Heating Elements	2 x 12kW	2 x 12kW	2 x 12kW
Volts Amps Watts	400v/32A/24kW	400v/32A/24kW	400v/32A/24kW
Shutdown System	Timed	Timed total stop	Timed
Max. Temperature	80°C	80°C	80°C
Water Tank Size	170lt	170lt	170lt
Weight	200kg	215kg	215kg
Dimensions (h x w x d)	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm